

**MITYLITE™ 1965Z0**



LED

2 alcaline AAA (incluse)

13,9 cm (5,48")



II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C Da

 RESA LUMINOSA	 DURATA UTILE	 DISTANZA DEL FASCIO	 INTENSITÀ DI PICCO DEL FASCIO	 IMPERMEABILE E SOMMERSIBILE
--	---	--	--	---

**Manufacturer:** Peli | **Category:** LED ATEX Flashlights  
**Country of origin:** US | **TARIC:** 85131000  
**MPH:** 1960-030-111E | **EAN:** 019428096502

**Dimensions exterior:** 13.9 cm

**Weight:** 0.06 kg

**Certifications:** CE Ex - II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C Da, Certificate: TRAC10ATEX11241X

**ATEX Certificate (PDF):** [Click here!](#)

**IP certificate (PDF):** [Click here!](#)

**STANAG certificate (PDF):** [Click here!](#)

**ATA certificate (PDF):** [Click here!](#)





**MIL certificate (PDF):** [Click here!](#)

#### Description/Features:

##### YOUR WORLDWIDE PASSPORT THROUGH HAZARDOUS LOCATIONS

While working in hazardous locations, remember a flashlight can be an ignition source. When you need the latest and brightest LED technology in a compact form factor, choose the new MityLite™ 1965 LED from Pelican. Small enough to fit in your shirt pocket, yet bright enough to illuminate your work area.

Long lasting, energy efficient, bright LEDs, along with a compact package make the new MityLite™ 1965 LED the safety approved light for the job.

FL1 STANDARD	HOCH
	21 Lumen
	4 h
	51 m
	756 cd